


ARBOR Wall



Sizes FORMATI	40x80 cm 15 3/4" x 31 1/2" \pm 10mm	
-------------------------	--	--

TECHNICAL FEATURES / CARATTERISTICHE TECNICHE	Requirements for nominal size N Requisiti per dimensione nominale N		ARBOR WALL
	7 cm \leq N < 15 cm	N \geq 15 cm	
	(mm)	(%) (mm)	
e.c. \pm 0,75	e.c. \pm 0,5	e.c. \pm 2,0	
w. \pm 0,75	w. \pm 0,5	w. \pm 2,0	
	EN 14411 annex G (Group Bla) EN 14411 appendice G (Gruppo Bla)	ISO 13006 annex G (Group Bla) ISO 13006 appendice G (Gruppo Bla)	

(*) The permissible deviation, in % or mm, of the average size for each tile (2 or 4 sides) from work size (W).
 (**) The permissible deviation, in % or mm, of the average thickness for each tile from the work size thickness (W).
 (***) The maximum permissible deviation from straightness, in % or mm, related to the corresponding work sizes (W).
 (****) The maximum permissible deviation from rectangularity, in % or mm, related to the corresponding work sizes (W).
 c.c. The maximum permissible deviation from centre curvature, in % or mm, related to diagonal calculated from the work sizes (W).
 e.c. The maximum permissible deviation from edge curvature, in % or mm, related to the corresponding work sizes (W).
 w The maximum permissible deviation from warpage, in % or mm, related to diagonal calculated from the work sizes (W).
 (1) Requirements european standard EN 176.
 (2) Determination of slip resistance of pedestrian surfaces; it does not cover sports surfaces and road surfaces for vehicles (skid resistance).
 Anti-slip performance is guaranteed at the time of delivery of the product

www.atlasconcorde.com